

■ チューブリングス表(TY/DW/SP/TP) 樹脂チューブ(丸型)のみ

| | チューブ径 | | | | |
|---------------|---------|-----|-----|-----|-----|
| | φ13 | φ15 | φ19 | φ22 | φ25 |
| 目安内容量 (mL) | 肩下長(mm) | | | | |
| 3.5 | 40 | | | | |
| 4.5 | 45 | | | | |
| 5.0 | 50 | | | | |
| 5.5 | 55 | | | | |
| 6.0 | 60 | 45 | | | |
| 6.5 | | 50 | | | |
| 7.0 | | 55 | | | |
| 8.0 | | 60 | 50 | | |
| 8.5 | | | 55 | | |
| 9.0 | | 65 | | | |
| 9.5 | | 70 | | | |
| 10.0 | | | 60 | | |
| 10.5 | | 75 | | 55 | |
| 11.0 | | 80 | 65 | | |
| 12.0 | | | | | |
| 13.0 | | | | 60 | |
| 13.5 | | | | | |
| 14.0 | | | 75 | | |
| 15.0 | | | 80 | 65 | |
| 16.0 | | | | | 60 |
| 16.5 | | | 85 | | |
| 17.0 | | | | | |
| 18.0 | | | 90 | | 65 |
| 19.0 | | | 95 | | |
| 20.0 | | | | 80 | |
| 20.5 | | | 100 | | 70 |
| 21.5 | | | | | |
| 23.0 | | | 110 | | 75 |
| 25.0 | | | 115 | 95 | 80 |
| 26.5 | | | | | |
| 27.5 | | | | | 85 |
| 28.0 | | | | | |
| 30.0 | | | | 110 | 90 |
| 35.0 | | | | 120 | 100 |
| 40.0 | | | | | 110 |
| 46.0 | | | | | 125 |

| | チューブ径 | | | | | |
|---------------|-------------|-----|-----|-----|-----|-----|
| | φ26 エアレス | φ30 | φ35 | φ40 | φ45 | φ50 |
| 目安内容量 (mL) | 肩下長(mm) | | | | | |
| 20 | 70 | | | | | |
| 25 | 80 | 70 | | | | |
| 30 | 90 | 75 | | | | |
| 35 | 100 | 80 | | | | |
| 40 | 110 | 85 | | | | |
| 45 | 120 | 95 | | | | |
| 50 | 130 | 105 | 80 | | | |
| 60 | | 120 | 95 | | | |
| 70 | | 140 | 105 | 90 | | |
| 80 | | | 115 | 100 | | |
| 90 | | | 125 | 110 | | |
| 100 | | | 135 | 120 | 100 | |
| 110 | | | 145 | 130 | 110 | |
| 120 | | | 160 | 140 | 120 | |
| 130 | | | | 150 | 125 | 100 |
| 140 | | | | 160 | 130 | 110 |
| 150 | | | | 170 | 140 | 120 |
| 160 | | | | | 145 | 130 |
| 170 | | | | | 150 | 140 |
| 180 | | | | | 160 | 145 |
| 190 | | | | | 165 | 155 |
| 200 | | | | | 170 | 160 |
| 210 | | | | | 185 | 165 |
| 220 | | | | | 195 | 170 |
| 230 | | | | | | 175 |
| 240 | | | | | | 180 |
| 250 | | | | | | 185 |
| 260 | | | | | | 190 |

- 上記数値はあくまでも参考値となります。
- ご採用に際しては、実際の内容物を充填しチューブ長をご確認願います。
- 適合キャップ、中栓、印刷範囲等の詳しい仕様は弊社担当にお問い合わせください。